




### TWIN SHAFT FLEKKIT

These fully flashed skylight kits can be a cost effective options for some multiple skylight situations. These units have two equal size shafts emanating from one larger skylight thereby reducing installation time and cost. Ideally these are used where two diffusers are desirable due to room aesthetics(a). They can also be used to provide light and ventilation to adjoining rooms in a single occupier dwelling(b).

- Ⓧ acrylic opal dome fixed to a fully flashed metal base
- Ⓧ 2 X highly reflective, u.v. resistant reinforced flexilight skylight shafts
- Ⓧ 2 X white ceiling trims
- Ⓧ 2 X diffusers (eggcrate for vented model; prismatic for non-vented model, vented prismatic model also available P.O.A.)

\*NOTE: 500 X 1200 skylight base used to suit 500 X 500 twin shaft  
600 X 1200 skylight base used to suit 600 X 600 twin shaft



### SELECTION CHART

SKYLIGHT SIZE (INTERNAL OPENING)	SHAFT SIZE	LIGHT AREA (m <sup>2</sup> )	STANDARD VENT AREA (m <sup>2</sup> )	BCA VENT AREA (m <sup>2</sup> )	EXTRA BCA VENT AREA (m <sup>2</sup> )
500 x 1200	2 off 500 x 500	0.50	0.144	0.312	0.370
600 X 1200	2 off 600 x 600	0.72	0.152	0.328	0.452

©The skylight system illustrations contained in this brochure are the sole property of Regent Skylight Systems Pty. Ltd and are reserved under copyright law. It is the responsibility of the user to ensure that the selected skylight system complies with the relevant building codes and authorities requirements. Regent Skylight Systems Pty. Ltd. reserves the right to improve or modify the skylight systems at any time. Zincalume® and Colorbond® are registered trademarks of BlueScope Steel Limited. Corrolux® is a registered trademark of Thomas Deutsch (Regent Sheet Metal Pty Ltd)

# REGENT SKYLIGHT SYSTEMS

PTY. LTD.

" The Ultimate in Skylights and Ventilation Products! "

[www.regentskylights.com.au](http://www.regentskylights.com.au)

MARCH 2016